

# TSW114

## GIGABIT DIN RAIL SWITCH

// TSW114 is an affordable way to simplify your connectivity with its plug-n-play nature.

// Compact size, front-facing ports, and an integrated DIN rail bracket enable easy installation across many industrial environments and especially control cabinets.

// 5 x Gigabit Ethernet ports provide stable, reliable connectivity for high-bandwidth solutions with multiple Ethernet devices.

// This rugged, anodized aluminum-housed unmanaged switch is the perfect choice for industrial solutions, boasting a wide power supply voltage range of 9-30 V with reverse polarity and voltage surge/transient protection.



### EASY MOUNTING

Integrated DIN rail bracket and front-facing ports

### GIGABIT ETHERNET

5 x Gigabit Ethernet ports with speeds of up to 1000 Mbps

### COMPACT & DURABLE

Rugged anodized aluminum housing that fits in your pocket

### PLUG-N-PLAY

No additional configuration needed



# KEY FEATURES

## HARDWARE

Power supply	2-pin industrial DC power socket, 9 - 30 VDC
Power consumption	Idle: 0.3 W / Max: 2.3 W
Status LEDs	1 x Power LED, 10 x LAN status LEDs
Ethernet	5 x RJ45 ports, 10/100/1000 Mbps
Ingress protection rating	IP30
Operating temperature	-40 °C to 75 °C
Housing	Anodized aluminum housing and panels
Dimensions	113.1 x 27.4 x 80.5 mm
Weight	174 g
Installation	Integrated DIN rail bracket, wall mounting (additional kit needed), flat surface placement

## PERFORMANCE SPECIFICATIONS

Bandwidth (Non-blocking)	10 Gbps
Packet buffer	128 KB
MAC address table size	2K entries
Jumbo frame support	9216 bytes

### FRONT VIEW

### BACK VIEW

